

# RIGID UNBRAKED AXLE 1,500 KG PLUS

## 112x5



### TECHNOLOGY

Model: PLUS  
 Axle type: LS 1500  
 Axle load: SA 1,500 kg  
 Wheel connection: 112x5 – M12x1.5

### SCOPE OF DELIVERY

I Wheel bolts loose

### SURFACE TREATMENT

I Axle profile hot-dip galvanised






### ACCESSORIES

I See following pages

**Comply with installation guidelines!**



**SAP:** ACHSE STARR UBR EA 1500 PLUS

OHF in mm	BC in mm	Single axle with wheel connection 112x5 RIGID UBR PLUS LS 1500	Single axle with wheel connection 112x5 watertight RIGID UBR PLUS LS 1500 WD					
		Wheel bolts Ball M 12x1.5 Axle cpl.	Wheel bolts Ball M 12x1.5 Axle cpl.					
1,150	700	200 578 01	200 579 01		24	-	50	15
1,200	750	200 578 02	200 579 02		24.5	-	50	15
1,250	800	200 578 03	200 579 03		24.9	-	50	15
1,300	850	200 578 04	200 579 04		25.3	-	50	15
1,350	900	200 578 05	200 579 05		25.7	-	50	15
1,400	950	200 578 06	200 579 06		26.2	-	50	15
1,450	1,000	1 422 441	200 579 07		26.6	-	50	15
1,500	1,050	200 578 07	200 579 08		27	-	50	15
1,550	1,100	200 578 08	200 579 09		27.5	-	50	15
1,600	1,150	200 578 09	200 579 10		27.9	-	50	15
1,650	1,200	200 578 10	200 579 11		28.3	-	50	15
1,700	1,250	200 578 11	200 579 12		28.7	-	50	15
1,750	1,300	200 578 12	200 579 13		29.2	-	50	15
1,800	1,350	200 578 13	200 579 14		29.6	-	50	15
1,850	1,400	200 578 14	200 579 15		30	-	50	15
1,900	1,450	200 578 15	200 579 16		30.4	-	50	15
1,950	1,500	200 578 16	200 579 17		30.9	-	50	15
2,000	1,550	200 578 17	200 579 18		31.3	-	50	15
2,050	1,600	200 578 18	200 579 19		31.7	-	50	15
2,100	1,650	200 578 19	200 579 20		32.2	-	50	15
2,150	1,700	200 578 20	200 579 21		32.6	-	50	15
2,200	1,750	200 578 21	200 579 22		33	-	50	15
2,250	1,800	200 578 22	200 579 23		33.4	-	50	15
2,300	1,850	200 578 23	200 579 24		33.9	-	50	15
2,350	1,900	200 578 24	200 579 25		34.3	-	50	15

