

RIGID UNBRAKED AXLE 1,800 KG PLUS

112x5



TECHNOLOGY

Model: PLUS
 Axle type: BS 1800
 Axle load: SA 1,800 kg
 Wheel connection: 112x5 – M12x1.5

SCOPE OF DELIVERY

┆ Wheel bolts loose

SURFACE TREATMENT

┆ Axle profile hot-dip galvanised





ACCESSORIES

┆ See following pages

Comply with installation guidelines!



SAP: ACHSE STARR UBR EA 1800 PLUS

| OHF in mm | BC in mm | Axle cpl. | Single axle with wheel connection 112x5 RIGID UBR PLUS BS 1800 | | | |
|-----------|----------|------------|---|---|---|---|
| | | | Wheel bolts Ball M 12x1.5 | | | |
| | | |  |  |  |  |
| 1,200 | 700 | 200 580 01 | 34.3 | - | 50 | 15 |
| 1,250 | 750 | 200 580 02 | 34.8 | - | 50 | 15 |
| 1,300 | 800 | 200 580 03 | 35.3 | - | 50 | 15 |
| 1,350 | 850 | 200 580 04 | 35.8 | - | 50 | 15 |
| 1,400 | 900 | 200 580 05 | 36.4 | - | 50 | 15 |
| 1,450 | 950 | 200 580 06 | 36.9 | - | 50 | 15 |
| 1,500 | 1,000 | 1 422 437 | 37.4 | - | 50 | 15 |
| 1,550 | 1,050 | 200 580 07 | 37.9 | - | 50 | 15 |
| 1,600 | 1,100 | 200 580 08 | 38.4 | - | 50 | 15 |
| 1,650 | 1,150 | 200 580 09 | 39 | - | 50 | 15 |
| 1,700 | 1,200 | 200 580 10 | 39.5 | - | 50 | 15 |
| 1,750 | 1,250 | 200 580 11 | 40 | - | 50 | 15 |
| 1,800 | 1,300 | 200 580 12 | 40.5 | - | 50 | 15 |
| 1,850 | 1,350 | 200 580 13 | 41 | - | 50 | 15 |
| 1,900 | 1,400 | 200 580 14 | 41.6 | - | 50 | 15 |
| 1,950 | 1,450 | 200 580 15 | 42.1 | - | 50 | 15 |
| 2,000 | 1,500 | 200 580 16 | 42.6 | - | 50 | 15 |
| 2,050 | 1,550 | 200 580 17 | 43.1 | - | 50 | 15 |
| 2,100 | 1,600 | 200 580 18 | 43.6 | - | 50 | 15 |
| 2,150 | 1,650 | 200 580 19 | 44.1 | - | 50 | 15 |
| 2,200 | 1,700 | 200 580 20 | 44.7 | - | 50 | 15 |
| 2,250 | 1,750 | 200 580 21 | 45.2 | - | 50 | 15 |
| 2,300 | 1,800 | 200 580 22 | 45.7 | - | 50 | 15 |
| 2,350 | 1,850 | 200 580 23 | 46.2 | - | 50 | 15 |
| 2,400 | 1,900 | 200 580 24 | 46.7 | - | 50 | 15 |

