

UNBRAKED AXLE 1,800 KG PLUS

112x5



TECHNOLOGY

Model: PLUS
 Axle type: 1800-9 PLUS
 Axle load: SA 1,800 kg
 Wheel connection: 112x5
 Suspension: Hexagonal rubber suspension
 Swing arm: 175 mm
 Wheel bearing: Compact bearing
 Rim centre hole: Min. 66.5 mm

SCOPE OF DELIVERY

┃ Wheel bolts loose
 ┃ Operating instructions

SURFACE TREATMENT

┃ Axle profile hot-dip galvanised



SAP: ACHSE GU UBR EA 1800 PLUS

OHF in mm	BC in mm	Single axle 112x5			
		Wheel bolts Ball M 12x1.5			
		Axle cpl.			
1,400	900	200 570 01	58	–	30
1,450	950	200 570 02	58	–	30
1,500	1,000	1 421 520	58	–	30
1,540	1,040	200 570 03	59	–	30
1,570	1,070	200 570 04	59	–	30
1,600	1,100	200 570 05	59	–	30
1,650	1,150	200 570 06	59	–	30
1,700	1,200	200 570 07	60	–	30
1,720	1,220	200 570 08	60	–	30
1,750	1,250	200 570 09	60	–	30
1,810	1,310	200 570 10	60	–	30
1,850	1,350	200 570 11	60	–	30
1,900	1,400	200 570 12	61	–	30
1,950	1,450	200 570 13	61	–	30
2,000	1,500	200 570 14	61	–	30
2,030	1,530	200 570 15	61	–	30
2,050	1,550	200 570 16	62	–	30
2,080	1,580	200 570 17	62	–	30
2,100	1,600	200 570 18	62	–	30
2,125	1,625	200 570 19	62	–	30
2,170	1,670	200 570 20	62	–	30
2,200	1,700	200 570 21	63	–	30
2,250	1,750	200 570 22	63	–	30
2,300	1,800	200 570 23	63	–	30
2,350	1,850	200 570 24	63	–	30

