

# BRAKED AXLES, SQUARE

## (SWING RUBBER SUSPENSION AXLES)

Axle load 2,000 kg, wheel brake S 2505-7 RASK\*



FIRST AXLE incl. loose brake cables

SECOND AXLE FOR TANDEM incl. welded adapter bracket (without brake cables)\*

Order No. Axle incl. loose brake cables CB 1805   5/ø112/R12	Reference No. Axle incl. loose brake cables CB 1805   5/ø112/R12	Order No. Second axle for tandem incl. welded adapter bracket (without brake cables)* CB 1805   5/ø112/R12	Reference No. Second axle for tandem incl. welded adapter bracket (without brake cables)* CB 1805   5/ø112/R12	FL	SP	Dimensions [mm]			Weight [kg]
						AM	L	G	
4021508	-	4021517	-	1515	1445	1000	1180	1620	78
4021509	-	4021518	-	1615	1545	1100	1280	1720	79
4021510	-	4021519	-	1715	1645	1200	1380	1820	80
4021511	-	4021520	-	1815	1745	1300	1480	1920	81
4021512	-	4021521	-	1915	1845	1400	1580	2020	82
4021513	-	4021522	-	2015	1845	1500	1580	2120	83
4021514	-	4021523	-	2115	2045	1600	1680	2220	84
4021515	-	4021524	-	2215	2145	1700	1780	2320	85
4021516	-	4021525	-	2315	2245	1800	1980	2420	86

\*only with limited tyre radius (Rmin = 0.27 m / Rmax = 0.321 m)

Mounting part kit for single-axle brake rod, see Accessories

Shock absorbers, see Accessories

